



OUTDOOR LIGHTING

LED FLOODLIGHTS

- ✓ High Technology
- ✓ Modern Design
- ✓ Efficiency
- ✓ 5 -Years Warranty

Applications


- Stores
- Rooms
- Restaurants
- Conferences
- Supermarkets
- Schools
- Libraries
- Hospitals
- Hotels

LED FLOODLIGHTS




Polar Diagram

60°



Polar Diagram

90°



GL-FLE-50



GL-FLE-60



3000K



4000K



5700K

Operang V oltag

AC90-305V

Model	LED Chip Brand	LED (pcs)	Designation	Colour Temp.(°K)	CRI	Rated Power (W)	Operating voltage	Luminous Flux (±10%)	Beam Angle	Product Dimensions (mm)
GL-FLE-40-03	Philips	18pc	warm white	3000°K	>80	40W	AC90-305V	5200	30°/60°/90°/120°	267x305x122
GL-FLE-40-04	Philips	18pc	cool white	4000°K	>80	40W	AC90-305V	5200	30°/60°/90°/120°	267x305x122
GL-FLE-40-05	Philips	18pc	day light	5700°K	>80	40W	AC90-305V	5200	30°/60°/90°/120°	267x305x122
GL-FLE-50-03	Philips	18pc	warm white	3000°K	>80	50W	AC90-305V	6500	30°/60°/90°/120°	267x305x122
GL-FLE-50-04	Philips	18pc	cool white	4000°K	>80	50W	AC90-305V	6500	30°/60°/90°/120°	267x305x122
GL-FLE-50-05	Philips	18pc	day light	5700°K	>80	50W	AC90-305V	6500	30°/60°/90°/120°	267x305x122
GL-FLE-60-03	Philips	18pc	warm white	3000°K	>80	60W	AC90-305V	7200	30°/60°/90°/120°	267x305x122
GL-FLE-60-04	Philips	18pc	cool white	4000°K	>80	60W	AC90-305V	7200	30°/60°/90°/120°	267x305x122
GL-FLE-60-05	Philips	18pc	day light	5700°K	>80	60W	AC90-305V	7200	30°/60°/90°/120°	267x305x122

Features



IP 67
IK 10

available also
in 1-10V
Dimmable

Power factor
>0,95

warranty
5
years

material
Aluminum alloy

Line Freq
50-60 Hz

